



## REWI Vakuu-Tumbler 180 – 700 MCB

Our advantages:

- wide range of uses thanks to VDU control
- all functions acoustically monitored by Computer
- integral vacuum system
- degerminating unit
- chilled germ-free, fresh air
- variable rpm (drum forwards and reverse)
- variable vacuum
- variable temperature (chilling tumbler) -15+5 degrees
- automatic zero-positioning of the drum
- drum filler hole eccentric
- computer monitored and removable brine separator
- automatic discharge device



250MCB



400MCB



700MCB



Control MCB

### REWI-Tumbler

Type	Capacity approx. kg	Height mm	Width mm	Lenght kg	Weight kg	Vacuum range %	Total output KW
130MCB	75	1' 300	600	1' 000	140	1- 99	1.5
180MCB	100	1' 300	750	1' 200	180	1- 99	1.5
250MCB	150	1' 450	750	1' 350	280	1- 99	1.85
400MBC	240	1' 450	870	1' 450	380	1- 99	2.2
700MBC	420	1' 450	870	1' 700	500	1- 99	2.2
1300MBC	800	2' 000	1' 350	2' 350	850	1- 99	4.5
2000MBC	1' 200	2' 000	1' 350	2' 500	1' 100	1- 99	4.5
3200MBC	1'900	2' 300	1'720	2' 550	1' 450	1- 99	5.5
6500MBC	3.500	2'665	1'910	3' 550	2' 200	1- 99	7.0